

Seaview Mounting Options for the GX-9 Antenna

Use the ADA-S5 Adaptor Plate with any of these popular Seaview
Vertical/AFT/FWD Mounts.

Vertical Mounts

AM5-M1	5"
AM5-M1SR	5"*
AM12-M1	12"
AM18-M1	18"

*16 degree angled base for Sea Rays



AFT Leaning Mounts

PMA-57-M1	5"
PMA-107-M1	10"
PMA-167-M1	16"
PMA-247-M1	24"
PMA-367-M1	36"



FWD Leaning Mounts

PMF-57-M1	5"
PMF-107-M1	10"



Pole Mount

RM8148-GX9	104" (8 feet)
------------	---------------

(no adapter plate needed)



All mounts above support SP1-MOD spreader Kit and LTB-S Lightbar & Lightbar tops



The right solutions for your maritime communications

Dual Mounts

PMA-DM1-M2 13.25" dual mount for closed dome radar and GX-9

PMA-DM2-M2 23.75" dual mount for open array radar and GX-9

These mounts require the ADA-S5 adapter plate

These dual mounts support the SP2-MOD spreader Kit and LTB-S Lightbar & Lightbar tops



Mast Mount

SM-GX9 (no adapter plate needed)



Keep the Above Deck Unit (ADU) which houses the GX-9 antenna away from other sources of RF radiation (antennas) as well as structures that can block reception of the satellite signal. Install the ADU with clear line of sight to the sky and the horizon.

The following rules should be followed:

- Install the ADU away from sources of heat, smoke, dust, shock or vibration
- The ADU should be installed 3m from VHF antennas
- The ADU should be installed 5 m from MF/HF antennas
- The ADU should be installed away from onboard radar scanners and outside their transmission
 - At least 5m to the side or down 30 dB down from the main beam
- The ADU should be installed 5m from direction finders



SeaviewGlobal.com, SeaviewEurope.com and Seaview are trademarks of PYI, INC

Telephone: 425-355-3669 Toll Free: 800-523-7558 Fax: 425-355-3661 Address: 12532 Beverly Park Rd, Lynnwood, WA 98087-1524

Europe Office: Tel / Fax (33) (0) 494 53 2770 Address: Z.I. Du Capitou, 85 Rue Louis Lepine, Frejus 83600 France